

# Especificaciones

MODELO			MFZ-KT25VG	MFZ-KT35VG	MFZ-KT50VG	MFZ-KT60VG
Unidad interior			MFZ-KT25VG	MFZ-KT35VG	MFZ-KT50VG	MFZ-KT60VG
Unidad exterior			SUZ-M25VA	SUZ-M35VA	SUZ-M50VA	SUZ-M60VA
Capacidad	Frío Nominal (Mín-Máx)	kW	2,5 (1,6-3,2)	3,5 (0,9-3,9)	5 (1,2-5,6)	6,1 (1,7-6,3)
	Calor Nominal (Mín-Máx)	kW	3,4 (1,3-4,2)	4,3 (1,1-5,0)	6 (1,5-7,2)	7 (1,6-8,0)
	kCal/h (frío)	kCal/h	2.150	3.010	4.300	5.246
	kCal/h (calor)	kCal/h	2.924	3.698	5.160	6.020
Consumo Nominal	Frío	kW	0,62	1,06	1,55	1,84
	Calor	kW	0,91	1,26	1,86	2,18
Consumo eléctrico anual*	Frío	kWh/año	134	185	257	343
	Calor (zona climática intermedia)	kWh/año	732	825	1.432	1.568
	Calor (Zona climática cálida)	kWh/año	–	–	–	–
EER / COP			4,00 / 3,71	3,30 / 3,41	3,21 / 3,21	3,30 / 3,21
Coeficiente energético*	SEER (Etiqueta)		6,5 (A++)	6,6 (A++)	6,8 (A++)	6,2 (A++)
	SCOP (Etiqueta) Zona climática intermedia		4,2 (A+)	4,4 (A+)	4,2 (A+)	4,1 (A+)
	SCOP (Etiqueta) Zona climática cálida		–	–	–	–

<b>MODELO</b>		<b>MFZ-KT25VG</b>	<b>MFZ-KT35VG</b>	<b>MFZ-KT50VG</b>	<b>MFZ-KT60VG</b>	
<b>Unidad Interior</b>	<b>Caudal de aire (Silencio / Baja / Media / Alta )</b>	<b>m³/min</b>	3,9 / 4,8 / 6,5 / 7,8 / 8,9	3,9 / 4,8 / 6,5 / 7,8 / 8,9	5,6 / 6,7 / 8,6 / 10,4 / 12,3	5,6 / 8,0 / 9,6 / 12,3 / 15,0
	<b>Nivel sonoro (Silencio / Baja / Media / Alta)</b>	<b>dB(A)</b>	19 / 24 / 31 / 37 / 41	19 / 24 / 31 / 37 / 41	28 / 32 / 37 / 42 / 48	28 / 36 / 40 / 46 / 53
	<b>Potencia sonora</b>	<b>dB(A)</b>	54	54	60	65
	<b>Dimensiones alto x ancho x fondo</b>	<b>mm</b>	600 x 750 x 215	600 x 750 x 215	600 x 750 x 215	600 x 750 x 215
	<b>Peso</b>	<b>kg</b>	14,5	14,5	14,5	15
	<b>Caudal de aire</b>	<b>m³/min</b>	36,3	34,3	45,8	50,1
<b>Unidad Exterior</b>	<b>Nivel sonoro</b>	<b>dB(A)</b>	45	48	48	49
	<b>Potencia sonora</b>	<b>dB(A)</b>	59	59	64	65
	<b>Dimensiones alto x ancho x fondo</b>	<b>mm</b>	550 x 800 x 285	550 x 800 x 285	714 x 800 x 285	880 x 840 x 330
	<b>Peso</b>	<b>kg</b>	30	35	41	54
	<b>Refrigerante R32</b>	<b>Pre-carga kg / PCA / TCO<sub>2</sub> eq</b>	0,65 / 675 / 0,44	0,9 / 675 / 0,6	1,2 / 675 / 0,81	1,25 / 675 / 0,84
	<b>Tensión/Fases – Intensidad Máxima</b>	<b>V/F – A</b>	230/1 – 7,0	230/1 – 8,7	230/1 – 14	230/1 – 15,4
<b>Diám. tuberías líquido/gas</b>	<b>mm</b>	6,35 / 9,52	6,35 / 9,52	6,35 / 12,7	6,35 / 15,88	
<b>Long. Máx. tubería vert/total</b>	<b>m</b>	12/20	12/20	30/30	30/30	

MODELO			MFZ-KT25VG	MFZ-KT35VG	MFZ-KT50VG	MFZ-KT60VG
Rango de operación	T <sup>a</sup> exterior para refrigeración	°C	-10 ~ +46	-10 ~ +46	-15 ~ +46	-15 ~ +46
	T <sup>a</sup> exterior para calefacción	°C	-10~ +24	-10~ +24	-10~ +24	-10~ +24

